

# ANTIQUE TRACTOR TIRES



> **GOODYEAR  
DYNA TORQUE**

Reduced vibration in field and road service and improved traction from its three-pitch tread design



MADE BY TITAN®



## TIRES TO COMPLETE THE PACKAGE

Having the right tires can give your antique tractor the true-to-period look. Titan tire and Goodyear Farm Tires offer the most complete lineup of tires for you antique tractor. With a broad range of sizes and styles, you can be sure we have the tire to match the machine - whether it's a John Deere Massey, Farmall®, Case, or otherwise.



### TITAN REARS

#### HI-TRACTION LUG

#### HI-POWER LUG

#### FARM TRACTOR

- Great size range for antique and older tractors.
- 45 degree lug provides self-cleaning and traction benefits.

Size	Titan Part Number	TL/TT	Load Rating	Max Load (lb)	Inflation Pressure (psi)	Design Rim Width (in)	Approved Alternate Rim Contour	Overall Width (in)	Outside Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Weight (lb)	Tread Depth (32 <sup>nd</sup> in)
------	-------------------	-------	-------------	---------------	--------------------------	-----------------------	--------------------------------	--------------------	-----------------------	---------------------------	--------------------	-------------	-----------------------------------

#### HI-TRACTION LUG

9.5-24	48D694	TL	6	1,870	30	8.00	W7, W8, W8H	9.4	42	19.8	126	67	41
15.5-38	47D874	TT	8	4,080	26	14.00	W14L, W14A	15.9	62.7	29.3	189	186	46

#### HI-POWER LUG

11.2-38	473408	TT	4	2,090	18	10.00	W10	11.6	57.5	27.1	174	114	42
11.2-38	483408	TL	4	2,090	18	10.00	W10	11.6	57.5	27.1	174	120	42
11.2-38	483608	TL	6	2,540	26	10.00	W10	11.6	57.5	27.1	174	122	42
12.4-38	473418	TT	4	2,340	16	11.00	W11, DW11A, W10	12.9	59.6	28.0	181	138	44
13.6-38	473628	TT	6	3,300	22	12.00	W12, DW12A, W11	14.1	61.6	28.8	186	150	46
14.9-28	48D638	TL	6	3,200	20	13.00	W12, W13	15.7	54.1	24.8	163	139	47

#### FARM TRACTOR

11.2-34	470402	TT	4	1,980	18	10.00	W10, W9	11.6	53.4	25.1	164	97	41
11.2-36	470406	TT	4	2,040	18	10.00	W9	11.2	55.4	26.1		93	44
12.4-36	470616	TT	6	2,830	24	11.00	W11	12.6	57.1	26.4	171	131	44
13.9-36	470693	TT	6	3,200	20	12.00	W12	14.2	58.7	27.4	178	133	44



### TITAN FRONTS

#### TRU-TRAC

#### MULTI-RIB

- Penetrates deep into the soil for maximum steering control.
- Minimal lateral side-slip because of its high center rib.

Size	Titan Part Number	TL/TT	Load Rating	Max Load (lb)	Inflation Pressure (psi)	Design Rim Width (in)	Approved Alternate Rim Contour	Overall Width (in)	Outside Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Weight (lb)	Tread Depth (32 <sup>nd</sup> in)
------	-------------------	-------	-------------	---------------	--------------------------	-----------------------	--------------------------------	--------------------	-----------------------	---------------------------	--------------------	-------------	-----------------------------------

#### TRU-TRAC

5.50-16SL	462239	TT	6	1,050	56	4.00	4.25KA, 4.50E	6.3	27.9	13.1	83	19	17
6.00-16SL	462375	TL	6	1,140	52	4.00	4.25KA, 4.50E	6.7	29.0	13.6	86	23	18
6.50-16SL	462381	TL	6	1,230	48	4.50	6LB	7.3	29.8	13.9	89	26	20
7.50-16SL	462284	TT	8	1,710	56	5.50	6LB	8.6	31.6	14.7	94	32	23
7.50-18SL	462278	TT	6	1,610	44	5.50	N/A	8.6	33.9	15.8	101	34	23
7.50-20SL	462393	TL	6	1,710	44	5.50	6LB	8.6	35.8	16.8	107	40	23

#### MULTI-RIB

7.50-16SL	466383	TL	6	1,480	44	5.50	6LB	8.5	31.3	14.6	93	36	21
-----------	--------	----	---	-------	----	------	-----	-----	------	------	----	----	----





## GOODYEAR REARS

### DURA TORQUE

- Excellent roadability provided by overlapping center lugs, long wear, and durability from its braced lug design and easy lug cleanability.

Size	Titan Part Number	TL/TT	Load Rating	Max Load (lb)	Inflation Pressure (psi)	Design Rim Width (in)	Approved Alternate Rim Contour	Overall Width (in)	Outside Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Weight (lb)	Tread Depth (32 <sup>nd</sup> in)
<b>DURA TORQUE</b>													
9.5-24	4DQ694	TL	6	1,870	30	8.00	W7, W8, W8H	9.4	41.3	19.2	123	67	36



## GOODYEAR FRONTS

### TRIPLE RIB HD

### TRIPLE RIB RS


- Three rib design provides strong steering capabilities in loose, cultivated soil.
- Excellent wear characteristics from the even load distribution on the center and shoulder ribs.

Size	Titan Part Number	TL/TT	Load Rating	Max Load (lb)	Inflation Pressure (psi)	Design Rim Width (in)	Approved Alternate Rim Contour	Overall Width (in)	Outside Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Weight (lb)	Tread Depth (32 <sup>nd</sup> in)
<b>TRIPLE RIB HD</b>													
4.00-19SL	TRR233	TT	4	715	52	3.00	N/A	4.4	28.3	13.6	87	16	11
5.00-15SL	TRR335	TL	4	715	44	3.00	4J	5.7	26.1	11.5	77	16	12
<b>TRIPLE RIB HD</b>													
6.50-16SL	TRD381	TL	6	1,230	48	4.50	4.00E, 4.25KA, 5.50F	6.9	30.0	13.9	89	29	18
7.50-16SL	TRD284	TT	8	1,710	56	5.50	6LB	8.4	32.4	15.1	96	34	18

# FFA TRACTOR RESTORATION PROGRAM

## Tire Donations Support Student Projects

Titan International, Inc. is proud to support the Future Farmers of America (FFA) and the restoration of antique tractors. FFA members can register to qualify for a donation of front and rear Titan or Goodyear tractor tires for their antique tractor. In 2014 alone, Titan International, Inc. donated more than 1,000 antique tractor tires for FFA members' restoration projects.



> <https://www.titan-intl.com/antique-tractor-restoration>



> **FOR EVERY APPLICATION, TITAN KEEPS YOU MOVING.**



1 (800) 872-2327 | [www.titan-intl.com](http://www.titan-intl.com)



**AMERICAN ENGINEERED  
AND MANUFACTURED**