

TEARN

FARMALL

ANTIQUE TRACTOR TIRES

GOD

1041

GOODYEAR DURA TORQUE Excellent roadability provided by the overlapping of center lugs





TIRES TO COMPLETE THE PACKAGE

Having the right tires can give your antique tractor the true-to-period look. Titan tire and Goodyear Farm Tires offer the most complete line-up of tires for you antique tractor. With a broad range of sizes and styles, you can be sure we have the tire to match the machine - whether it's a John Deere^{*}, Massey Ferguson^{*}, Farmall^{*}, Case^{*}, or otherwise.



TITAN REARS

HI-TRACTION LUG R-1

- Exclusive long bar/medium bar tread pattern
- This design follows a symmetrical lug pattern to eliminate side-to-side rocking and promotes even wear

HI-POWER LUG R-1

- Single Bar design with wide overlapping lugs
- Deep Tread and excellent tread wear and durability
- Designed to deliver power to the ground
- Design offers maximum cleaning and side-hill slip resistance



- Great size for antique and older tractors
- The open 45-degree lug provides selfcleaning and traction benefits

Size	Catalog Number	TL/ TT	Ply Rating	Inflation Pressure (psi)	Rated Load (Ib)	Approved Rim	Overall Width (in)	Outside Diameter (in)	Static Loaded Radius (in)	Rolling Circumference (in)	Tread Depth (32 nd in)	Weight (lb)
HI-TRACT	HI-TRACTION LUG R-1											
13.6-28	48D624	TL	6	22	2,830	W10, W10L, DW10, W11, DW11, W12 , DW12	14.3	52.9	24.3	158	46	146
14.9-28	48D038	TL	10	32	4,180	W11, DW11, W12 , DW12, W13, DW13, DW13L	14.9	54.3	24.9	162	47	172
15.5-38	47D874	TT	8	26	4,080	W14L, DW14A	16.5	62.6	N/A	N/A	46	182
16.9-34	47D844	TT	8	24	4,680	W14L, DW14A, DW14L, W15L , DW15L, DD15L	17.8	63.0	29.0	188	48	192
16.9-38	47D820	TT	8	24	4,940	W14L, DW14A, DW14L, W15A , W15L, DW15L, DD15L	17.8	67.0	31.0	200	48	210
HI-POWE	R LUG R-1											
11.2-38	483408	TL	4	18	2,090	W10	11.5	58.1	27.5	176	42	119
12.4-38	473418	TT	4	16	2,340	W9, W10, W10L, DW10, W11 , DW11, DW11A	12.9	59.6	28.0	181	44	141
13.6-38	473628	TT	6	22	3,300	W10, W10L, DW10, W11, DW11, W12 , DW12, DW12A	14.3	61.2	28.8	185	46	150
14.9-26	483631	TL	6	20	3,080	W12 , DW12A	15.0	52.2	24.1	156	47	161
14.9-38	473673	TT	6	32	4,300	W12 , DW12A	15.7	64.7	N/A	N/A	47	187
FARM TR	ACTOR R-1											
11.2-36	470406	ΤT	4	18	2,040	W9	11.2	55.4	26.1	170	44	93

N/A - Information Not Currently Available



GOODYEAR REARS

DURA TORQUE R-1

- · Excellent roadability provided by the overlapping center lugs
- Traction in a wide range of sizes due to its long bar design
- Long wear and durability from its braced lug design
- Easy lug cleanability

Size	Catalog Number	TL/ TT	Ply Rating	Inflation Pressure (psi)	Rated Load (lb)	Approved Rim	Overall Width (in)	Outside Diameter (in)	Static Loaded Radius (in)	Rolling Circumference (in)	Tread Depth (32 nd in)	Weight (lb)
DURA TORQUE R-1												
9.5-24	4DQ694	TL	6	30	1,870	W7, W8 , W8H	9.6	41.5	19.2	124	36	69
18.4-34	47Q854	TT	8	20	5,080	W15L, DW15A, W16L, DW16A	18.8	65.1	29.6	194	52	243
18.4-38	47Q877	TT	8	20	5,360	W15L, W16A , DD16	18.8	69.1	32.1	205	52	257



TITAN FRONTS

NTS TRU-TRAC FRONT TRACTOR F-2

- Penetrates deep into soil for maximum steering control and minimal lateral side-slip because of its high center rib
 Used by original equipment manufacturers and offers
- Used by original equipment manufacturers and one excellent durability

TRU-TRAC MULTI-RIB F-2M

- Best for handling heavy loads on hard-packed surfaces
- Offers excellent load distribution and flotation
- Features a nylon carcass, durable tread compound and bead rim shield

Size	Catalog Number	TL/ TT	Ply Rating	Inflation Pressure (psi)	Rated Load (lb)	Approved Rim	Overall Width (in)	Outside Diameter (in)	Static Loaded Radius (in)	Rolling Circumference (in)	Tread Depth (32 nd in)	Weight (lb)
TRU-TRAC FRONT TRACTOR F-2												
5.50-16SL	462239	TT	6	56	1,050	4.00E , 4.25KA, 4.50E	6.0	27.5	N/A	N/A	17	21
6.00-16SL	462375	TL	6	52	1,140	4.00E, 4.25KA, 4.50E, 4 1/2KB	6.6	28.6	N/A	N/A	18	24
7.50-18SL	462278	TT	6	44	1,610	5.50F	8.5	33.3	N/A	N/A	23	38
TRU-TRAC MULTI-RIB F-2M												
9.5L-15SL	466343	TL	6	36	1,520	8LB	10.1	31.7	14.78	95	21	50

N/A - Information Not Currently Available



GOODYEAR FRONTS

- Improved steering in loose, cultivated soil provided
- by the deep, wide center ribs
- 3 rib design provides excellent steering capabilities
- Excellent wear characteristics from the even load distribution on the center and shoulder ribs

Size	Catalog Number	TL/ TT	Ply Rating	Inflation Pressure (psi)	Rated Load (lb)	Approved Rim	Overall Width (in)	Outside Diameter (in)	Static Loaded Radius (in)	Rolling Circumference (in)	Tread Depth (32 nd in)	Weight (lb)
TRIPLE RIB HD F-2												
7.50-16SL	TRD284	TT	8	56	1,710	5.50F, 6LB	8.6	32.6	N/A	N/A	18	34
10.00-16SL	TRD398	TL	8	44	2,340	W8L , 8LB	10.8	35.2	16.4	105	26	56

FFA TRACTOR RESTORATION PROGRAM Tire Donations Support Student Projects

Titan International, Inc. is proud to support the Future Farmers of America (FFA) and the restoration of antique tractors. FFA members can register to qualify for a donation of front and rear Titan or Goodyear tractor tires for their antique tractor. Since 1996 Titan International has donated thousands of tractor tires to FFA members' restoration projects.

https://www.titan-intl.com/antique-tractor-restoration



> FOR EVERY APPLICATION, TITAN KEEPS YOU MOVING.





1 (800) 872-2327 | www.titan-intl.com

TITAN MOVES THE WORLD* 010C01EN0402 © 2024 Titan International, Inc. All trademarks are owned by Titan International, Inc. other than the trademark GOODYEAR and the winged foot logo, which are owned by The Goodyear Tire & Rubber Company. Materials and specifications are subject to change without notice. John Deere is a registered trademark of Deere & Company. Massey Ferguson* is a worldwide brand of Agco. Farmall is a registered trademark of CNH America LLC. Case is a registered trademark of CNH America LLC.