

OPTITRAC

- · Latest generation compound and construction technology
- High flex carcass technology operates at up to 40% less inflation
- · Optimized tire and footprint shape for minimal soil compaction
- Continuous helical lug curvature for enhanced ride comfort
- Tuned asymmetric lug shape which improves traction and stability
- Premium tread depth for a long tire life and enhanced soil traction
- Modern sophisticated appearance with a distinctive look and decoration







OPTITRAC														
Tire Size	Catalog Number	TL/ TT	Load Rating	Rated Speed (mph)	Rated Inflation Pressure (psi)	Rated Load (lbs)	Recom'd Rim Width (in)	Overall Width (in)	Outside Diameter (in)	Static Loaded Radius (in)	Rolling Circ. (in)	Flat Plate Area (in ²)	Weight (lbs)	Tread Depth (32nd in)
LSW1100/35R32	G0PD11GY	TL	175D	40	23	15200	38	40.4	62.94	27.22	187	799	863	72

OPTITRAC - METRIC														
Tire Size	Catalog Number	TL/ TT	Load Rating	Rated Speed (km/h)	Rated Inflation Pressure (kpa)	Rated Load (kg)	Recom'd Rim Width (in)	Overall Width (mm)	Outside Diameter (mm)	Static Loaded Radius (mm)	Rolling Circ. (mm)	Flat Plate Area (cm ²)	Weight (kg)	Tread Depth (mm)
LSW1100/35R32	G0PD11GY	TL	175D	65	160	6900	38	1026.16	1598.68	691.39	4751	5154	391	57



